



Cathedral Flooring

# Cathedral Flooring

## 14mm Engineered


4mm veneer on 10mm WBP Pure Birch ply

Width	Species	Grade	Finish	Pack Size
180mm	European Oak	Character	UV Oil	2.16m <sup>2</sup>
180mm	European Oak	Character	Smoked Hardwax Oil	2.16m <sup>2</sup>
180mm	European Oak	Character	Rustic Hardwax Oil	2.16m <sup>2</sup>


Character grade has colour variation with sound filled knots. No sapwood allowed. Natural grade has colour variation with minimal knots. No sapwood allowed.

### INFORMATION

- FSC® Certified by Rainforest Alliance.
- 6mm Veneer bonded to ply by cold press method.
- 10mm Pure Birch plywood substrate "WBP" (Water and Boil Proof).
- 1mm Bevel on the long edge, no bevel on short edge.
- Board length 2.4m with 3 full and 1 split board per pack. This avoids a regular joint structure when the floor has been laid
- Can be floated.
- Must be fully bonded to a suitable substrate when used in conjunction with Underfloor Heating.
- Resistance 0.0823 m<sup>2</sup>k/w  
Conductivity 0.17 W/m.k  
Conductance 0023m<sup>2</sup>k/W  
Togg 0.824 togg



UV Oil



Smoked Oak



Rustic Oil



## Winchester Hardwood Flooring Limited

The Foundry, London Road, Kings Worthy, Winchester, Hampshire SO23 7QA  
Telephone +44 (0)1962 888577 Facsimile +44 (0)1962 888578  
e-mail enquiries@whfloors.co.uk www.whfloors.co.uk